142CON1

Serial No.: 10/600,133 Filed: June 20, 2003

Page : 2 of 10

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1.-36. (Cancelled)

37. (Currently Amended) A data-mirroring method comprising:

obtaining control from an I/O process executing on a host computer, the I/O process processing a first I/O request for writing data to a first device, wherein obtaining control from an I/O process comprises intercepting a call by a first module to a second module;

creating a second I/O request for writing the data to [the] a second device; and returning control to the I/O process.

- 38. (Previously Presented) The method of claim 37, further comprising determining that the first device is being mirrored by a second device.
- 39. (Previously Presented) The method of claim 37, wherein obtaining control from an I/O process comprises:

identifying a forward pointer to instructions to be executed by the I/O process in processing the first I/O request; and

causing the forward pointer to point to a front-end detour that includes instructions for creating the second I/O request.

Serial No.: 10/600,133 Filed: June 20, 2003

Page : 3 of 10

40. (Currently Amended) The method of claim 37, <u>further comprising selecting the first</u>

<u>module to be</u> [wherein obtaining control from an I/O process comprises intercepting a call

by] an IOSVSSCH module <u>and selecting the second module</u> to <u>be</u> a DDTSIO module.

41. (Currently Amended) The method of claim 37, wherein obtaining control from an I/O process comprises:

identifying a forward pointer that points to instructions for executing the second [a DDTSIO] module, and

causing the forward pointer to point to instructions for executing a front-end detour, the front-end detour including instructions for creating the second I/O request.

42. (Previously Presented) The method of claim 37, further comprising:

obtaining control from the I/O process after the first I/O request has been made available to a first data storage system managing the first device; and

obtaining information indicative of a status of the first I/O request.

43. (Previously Presented) The method of claim 37, further comprising:

identifying a return pointer to a module that is intended to receive information indicative of a status of the first I/O request; and

causing the return pointer to point to a back-end detour, the back-end detour including instructions for causing the second I/O request to be provided to a second data storage system managing the second device.

44. (Currently Amended) The method of claim 43, wherein identifying a return pointer comprises identifying a pointer to the first [an-IOSVSSCH] module.

Serial No.: 10/600,133 Filed: June 20, 2003

Page : 4 of 10

45. (**Previously Presented**) A computer-readable medium having encoded thereon software for executing a data-mirroring [computer-readable medium] method, said software comprising instructions for:

obtaining control from an I/O process executing on a host computer, the I/O process processing a first I/O request for writing data to a first device wherein the instructions for obtaining control from the I/O process comprise instructions for intercepting a call by a first module to a second module;

creating a second I/O request for writing the data to [the] a second device; and returning control to the I/O process.

- 46. (Previously Presented) The computer-readable medium of claim 45, wherein the software further comprises instructions for determining that the first device is being mirrored by a second device; and
- 47. (Previously Presented) The computer-readable medium of claim 45, wherein the instructions for obtaining control from an I/O process comprise instructions for:

identifying a forward pointer to instructions to be executed by the I/O process in processing the first I/O request; and

causing the forward pointer to point to a front-end detour that includes instructions for creating the second I/O request.

48. (Previously Presented) The computer-readable medium of claim 45, wherein the instructions for obtaining control from an I/O process comprise instructions for selecting the first module to be [intercepting a call by] an IOSVSSCH module and selecting the second module to be a DDTSIO module.

142CON1

Serial No.: 10/600,133 Filed: June 20, 2003

Page : 5 of 10

49. (Currently Amended) The computer-readable medium of claim 45, wherein the instructions for obtaining control from an I/O process comprise instructions for:

identifying a forward pointer that points to instructions for executing the first [a DDTSIO] module, and

causing the forward pointer to point to instructions for executing a front-end detour, the front-end detour including instructions for creating the second I/O request.

50. (**Previously Presented**) The computer-readable medium of claim **45**, wherein the software further comprises instructions for instructions for:

obtaining control from the I/O process after the first I/O request has been made available to a first data storage system managing the first device; and

obtaining information indicative of a status of the first I/O request.

51. (Previously Presented) The computer-readable medium of claim 45, wherein the software further comprises instructions for:

identifying a return pointer to a module that is intended to receive information indicative of a status of the first I/O request; and

causing the return pointer to point to a back-end detour, the back-end detour including instructions for causing the second I/O request to be provided to a second data storage system managing the second device.

52. (Currently Amended) The computer-readable medium of claim [32]51, wherein the instructions for identifying a return pointer comprise instructions for identifying a pointer to the first [an IOSVSSCH] module.

142CON1

Serial No.: 10/600,133 Filed: June 20, 2003

Page : 6 of 10

53. (New) A data-mirroring method comprising:

obtaining control from an I/O process executing on a host computer, the I/O process processing a first I/O request for writing data to a first device;

creating a second I/O request for writing the data to the second device; and returning control to the I/O process;

wherein obtaining control from an I/O process comprises:

identifying a forward pointer to instructions to be executed by the I/O process in processing the first I/O request; and

causing the forward pointer to point to a front-end detour that includes instructions for creating the second I/O request.

54. (New) A computer-readable medium having encoded thereon software for executing a data-mirroring method, said software comprising instructions for:

obtaining control from an I/O process executing on a host computer, the I/O process processing a first I/O request for writing data to a first device;

creating a second I/O request for writing the data to the second device; and returning control to the I/O process;

wherein, the instructions for obtaining control from an I/O process comprise instructions for:

identifying a forward pointer to instructions to be executed by the I/O process in processing the first I/O request; and

142CON1

Serial No.: 10/600,133 Filed : June 20, 2003 ... Page : 7 of 10

causing the forward pointer to point to a front-end detour that includes instructions for creating the second I/O request.